



Performance features

- HDF 68 Stil




- HDF 82-Systeme

Manufacturer:

Kneer GmbH - Fenster und Haustüren - Horst-Kneer-Straße 1 - 72589 Westerheim

SÜD-FENSTERWERK GmbH & Co. Betriebs-KG - Rothenburger Straße 39 - 91625 Schnelldorf

According to DIN EN 14351-1:

Performance characteristics		Single-sash window with downlight	Double-sash window	Single-sash balcony door
				
1.	Resistance against windload – test pressure and frame deflection	up to B3	up to B2	up to B3
2.	Driving rain resistance – unprotected	up to 7A	up to 4A	up to 7A
3.	Air permeability	3	3	3
4.	Heat transition coefficient U_w (W/m ² K)	0,71 - 1,5	0,71 - 1,5	0,71 - 1,5
5.	Sound protection	32-45dB	32-45dB	32-45dB
6.	Load capacity of safety devices	requirements fulfilled	requirements fulfilled	requirements fulfilled
7.	Hazardous substances	none	none	none
12.	Burglar resistance	up to RC 2	up to RC 2	up to RC 2

The indicated performance characteristics represent the product characteristics of the tested specimen. The possibility of combining performance characteristics shall be examined on a case-by-case basis. The values given may vary depending on the construction.

